

GA9040SK01 230mm Angle Grinders GA9040SK 2 600W





Rotatable gear housing Can be positioned at every 90° to suit most cutting and grinding applications



Torque limiter Protects lock nut from over-



Superior anti-dust structure
Protective zigzag varnish on armature coil.
Protective powder varnish-coating on field coil.
Bearings protected by labyrinth construction.
Vent slots designed to minimize dust entrance.

Large rubber tool rest Protects workpiece from scratches.



Heavy duty shaft



Rotatable rear handle Can be positioned at 90° left or right to suit most cutting and grinding operations.





Vibration absorbing rubber



SPECIFICATIONS:

Maximum Capacities:

Depressed centre wheel 230mm Continuous rating input 2 600W No load speed 6 600 r/min Overall length 503mm Net weight 6.7kg Power supply cord 2.5m Carbon brush AC204

FEATURES:

Double insulation Carry case Torque limiter Soft start

GA9040SK



Lock nut wrench & grip. Tool does not come with depressed centre wheel.

OPTIONAL ACCESSORIES

Description Part No. Diamond blade segmented A-84137 Diamond blade, corrugated A-84171 Inner flange 13-42 DIN45 224298-7 Lock nut 14-45 224543-0 Lock nut wrench 35 large 2 pin 782407-9 Rubber pad & nut B-00876 Safety cutting flange 191845-8 Sanding lock nut 14 -48 224515-5 Special lock nut 14-45 192567-3 (Prevents lock-up)



