

FS2300, FS4300 & FS6300 Drywall Screwdrivers for Timber, Aluminium 570W

& Steel Struts

makita

Aluminium gear housing

One-touch locator allows for easy locator installation / removal with a single action.

Exhaust vents
designed to prevent exhaust air
from blowing dust and debris
around when operating close to floor level

Reversing switch

Variable speed control by trigger switch.



LED job light convenient for operation in dark job sites.



Bit holder for spare bit storage.

Locator holder convenient for temporary storage of locator during operation



for quiet operation. Direct drive transmission in reverse rotation enables unscrewing without removing locator.

Durable belt clip composed of sheet metal sandwiched between plastic layers for added strength

Best possible tool body for screwdriving ergonomically designed to: minimize operator fatigue

- even during long continuous operation. maximizes power thrust.
- allows smoother and easier trigger pull.



Rubberized soft grip provides comfortable grip and more control, while minimizing operator fatigue

MAKITA ADVANTAGE

Model FS6300

Compact lightweight design

Well balanced for easy handling and maneuverability Shorter overall length for easy screwdriving.

First corded screwdrivers equipped with LED job light.

SPECIFICATIONS FS2300 FS4300 Fs6300 Application **Timber Struts** Steel Struts **Aluminium Struts** Capacities Drywall screw 5_{mm} 5mm 4mm Self drilling screw 6mm 6mm Driving shank 6.35mm hex 6.35mm hex 6.35mm hex Continuous rating input 570W 570W 570W No load speed 0 - 2 500r/min 0 - 4,500 r/min 0 - 6,000 r/min Overall dimensions 279 x 65 x 207mm LxWxH 290 x 70 x 207mm 279 x 65 x 207mm Net weight 1.6kg 1.4kg 1.4kg Power supply cord 2.5m 2.5m 2.5m Carbon brush CB419 CB419 **CB419 FEATURES:**

Double insulation	Yes	Yes	Yes
Reversing	Yes	Yes	Yes
Built-In job light	Yes	Yes	Yes
Variable speed	Yes	Yes	Yes

STANDARD EQUIPMENT:

O IT IN TO I CONTINUE IT IT				
Phillips insert bit	Yes	Yes	Yes	
Magnetic bit holder	Yes	Yes	Yes	



